

# DECLARATION OF PERFORMANCE

Nr 1/03/2018

1. Unique identification code of the product-type

EPS (STYROPOR) –  $\lambda$  (0,035) -  $\rho_a$  (28,5)

Permanent shuttering system for Izodom 2000 Polska wall elements

2. Intended use or uses :

*The product is intended for use in the construction of internal and external walls below and above the ground level. The walls can be of load-bearing (constructional) or non-load-bearing (non-structural) type, in accordance with the European technical assessment ETA-07/0117*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. not applicable

5. The system(s) of assessment and verification of constancy of performance: 2+

6a. not applicable

European technical assessment: ETA 07/0117

Technical evaluation unit: Deutsches Institut für Bautechnik DIBt

Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: height length, thickness,	$\pm 0,8 \%$ $\pm 0,8 \%$ $\pm 2 \text{ mm}$	EN 823 EN 822 EN 822	ETA 07/0117 ETAG 009
Declared thermal conductivity coefficient $\lambda$	$\leq 0,035 \text{ W/m}^2\text{K}$	EN 12667	ETA 07/0117 ETAG 009
Apparent density $\rho_a$	$> 28,5 \text{ kg/m}^3$	EN 1602	ETA 07/0117 ETAG 009
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010
The resistance of the wall element to concrete pressure	Tensile stress for 10s at a pressure of 0.40 bar	Test procedure PB-KJI-01	ETA 07/0117 ETAG 009



## 8. Resistance to fire

- According to the guidelines in ETAG 009 for permanent shuttering systems, Annex C: "Resistance to fire", Table 1 *Minimum thickness of the concrete infill in the case of wall exposed on one side*, continuous **systems with MCF, MCFU and MCFU - shuttering elements satisfy the criteria of load-bearing, tightness and fire insulation endurance REI 120.**
- According to the guidelines in ETAG 009 for permanent shuttering, Annex C "Resistance to fire", Table 2 *"Grid and column type load bearing walls, minimum dimension of vertical columns"*, continuous **systems with MC - shuttering elements - satisfy the criteria of fire load-bearing R30.**

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018

  
**IZODOM 2000 Polska Sp. z o.o.**  
**Vice-president Jakub Wójcik**

**IZODOM 2000 POLSKA Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A.  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414; REGON 730192247

**IZODOM 2000 POLSKA Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A.  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414; REGON 730192247

# DECLARATION OF PERFORMANCE

Nr 2/03/2018

1. Unique identification code of the product-type

EPS (NEOPOR) –  $\lambda$  (0,032) -  $\rho_a$  (28,5)

Permanent shuttering system for Izodom 2000 Polska wall elements

2. Intended use or uses :

*The product is intended for use in the construction of internal and external walls below and above the ground level. The walls can be of load-bearing (constructional) or non-load-bearing (non-structural) type, in accordance with the European technical assessment ETA-07/0117*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. not applicable

5. The system(s) of assessment and verification of constancy of performance: 2+

6a. not applicable

European technical assessment: ETA 07/0117

Technical evaluation unit: Deutsches Institut für Bautechnik DIBt

Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: height length, thickness,	$\pm 0,8 \%$ $\pm 0,8 \%$ $\pm 2 \text{ mm}$	EN 823 EN 822 EN 822	ETA 07/0117 ETAG 009
Declared thermal conductivity coefficient $\lambda$	$\leq 0,032 \text{ W/m}^2\text{K}$	EN 12667	ETA 07/0117 ETAG 009
Apparent density $\rho_a$	$> 28,5 \text{ kg/m}^3$	EN 1602	ETA 07/0117 ETAG 009
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010
The resistance of the wall element to concrete pressure	Tensile stress for 10s at a pressure of 0.40 bar	Test procedure PB-KJI-01	ETA 07/0117 ETAG 009



## 8. Resistance to fire

- According to the guidelines in ETAG 009 for permanent shuttering systems, Annex C: "Resistance to fire", Table 1 *Minimum thickness of the concrete infill in the case of wall exposed on one side*, continuous **systems with MCF, MCFU and MCFU - shuttering elements satisfy the criteria of load-bearing, tightness and fire insulation endurance REI 120.**
- According to the guidelines in ETAG 009 for permanent shuttering, Annex C "Resistance to fire", Table 2 *"Grid and column type load bearing walls, minimum dimension of vertical columns"*, continuous **systems with MC - shuttering elements - satisfy the criteria of fire load-bearing R30.**

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018

  
Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

„IZODOM 2000 POLSKA” Sp. z o.o.  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00 414, REGON 730192247



# DECLARATION OF PERFORMANCE

Nr 3/03/2018

1. Unique identification code of the product-type: MID-FLOOR ELEMENTS

EPS EN 13163 – T2-L3-W2-S5-P10-BS150-CS(10)100-  $\lambda$  (0,035)-TR150

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 150$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 200$ kPa	EN 826	
Tensile strength	TR $\geq 150$ kPa	EN 1607	
Declared thermal conductivity coefficient $\lambda$	0,035 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010

## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-69-50  
tel. (43) 823-69-47, pol./fax (43) 823-23-68  
NIP 726-00-00 414, REGON 730192247

# DECLARATION OF PERFORMANCE

Nr 4/03/2018

1. Unique identification code of the product-type: VENTED PANELS

EPS (STYROPOR) EN 13163- T2-L3-W2-S5-P10-BS150-CS(10)100-  $\lambda$ (0,035)-TR150

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 150$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 100$ kPa	EN 826	
Tensile strength	TR $\geq 150$ kPa	EN 1607	
Declared thermal conductivity coefficient $\lambda$	0,035 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010


## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

„IZODOM 2000 POLSKA” Sp. z o.o.  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-114, REGON 730142247



# DECLARATION OF PERFORMANCE

Nr 5/03/2018

1. Unique identification code of the product-type: VENTED PANELS

EPS (NEOPOR) EN 13163- T2-L3-W2-S5-P10-BS150-CS(10)100-  $\lambda$ (0,032)-TR150

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 150$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 100$ kPa	EN 826	
Tensile strength	TR $\geq 150$ kPa	EN 1607	
Declared thermal conductivity coefficient $\lambda$	0,032 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010

## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-69-50  
tel. (43) 823-69-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414, REGON 730192247

# DECLARATION OF PERFORMANCE

Nr 6/03/2018

1. Unique identification code of the product-type: INSULATION PANELS WITH GROUT  
EPS (STYROPOR) EN 13163- T2-L3-W2-S5-P10-BS150-CS(10)100-  $\lambda(0,035)$ -TR150

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 150$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 100$ kPa	EN 826	
Tensile strength	TR $\geq 150$ kPa	EN 1607	
Declared thermal conductivity coefficient $\lambda$	0,035 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010

zw


## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

„IZODOM 2000 POLSKA” Sp. z o.o.  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-69-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-114, REGON 730192247



# DECLARATION OF PERFORMANCE

Nr 7/03/2018

1. Unique identification code of the product-type: INSULATION PANELS WITH GROUT  
EPS (NEOPOR) EN 13163- T2-L3-W2-S5-P10-BS150-CS(10)100-  $\lambda$ (0,032)-TR150

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 150$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 100$ kPa	EN 826	
Tensile strength	TR $\geq 150$ kPa	EN 1607	
Declared thermal conductivity coefficient $\lambda$	0,032 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010


## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414; REGON 730192247



**Izodom 2000 Polska Sp. z o.o.**  
Vice-president Jakub Wójcik

# DECLARATION OF PERFORMANCE

Nr 8/03/2018

1. Unique identification code of the product-type: INSULATION PERIMETER PANELS 30  
EPS (PERIPOR) EN 13163- T2-L3-W2-S5-P10-BS250-CS(10)200-  $\lambda$ (0,035)

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 250$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 200$ kPa	EN 826	
Declared thermal conductivity coefficient $\lambda$	0,035 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010




## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414, REGON 730192247



# DECLARATION OF PERFORMANCE

Nr 9/03/2018

1. Unique identification code of the product-type: INSULATION PERIMETER PANELS 40  
EPS (PERIPOR) EN 13163- T2-L3-W2-S5-P10-BS500-CS(10)300-  $\lambda$ (0,034)

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 500$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 300$ kPa	EN 826	
Declared thermal conductivity coefficient $\lambda$	0,034 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010


## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414; REGON 730192247



**Izodom 2000 Polska Sp. z o.o.**  
**Vice-president Jakub Wójcik**

# DECLARATION OF PERFORMANCE

Nr 10/03/2018

1. Unique identification code of the product-type: ROOF INSULATION PANELS

EPS EN 13163- T2-L3-W2-S5-P10-BS150-CS(10)100-  $\lambda$ (0,035)-TR150

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 150$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 100$ kPa	EN 826	
Tensile strength	TR $\geq 150$ kPa	EN 1607	
Declared thermal conductivity coefficient $\lambda$	0,035 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010

## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



Izodom 2000 Polska Sp. z o.o.  
Vice-president Jakub Wójcik

**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414; REGON 730192247



# DECLARATION OF PERFORMANCE

Nr 11/03/2018

1. Unique identification code of the product-type: ROOF FOUNDATION SLAB ELEMENTS  
EPS (PERIPOR) EN 13163- T2-L3-W2-S5-P10-BS500-CS(10)300-  $\lambda(0,034)$

2. Intended use or uses :

*According to EN 13163 norm - for thermal insulation in construction.*

3. Manufacturer : IZODOM 2000 POLSKA Sp. Z o.o. Zduńska Wola 98-220 ul. Ceramiczna 2a

4. - not applicable

5. The system(s) of assessment and verification of constancy of performance: 3

6a. - Reference number of the harmonized standard – PN-EN 13163; 2013-05E

6b. -Notified body: Certification Department of Instytut Techniki Budowlanej No. 1488

7. Declared performances

Essential characteristics for the intended use, for thermal insulation in construction	Declared performance, class or level	Test standard	Harmonized technical specification
Dimensional tolerance: thickness length, width	T2 ( $\pm 2$ mm) L3 ( $\pm 0,6$ %) W2 ( $\pm 2$ mm)	EN 823 EN 822 EN 822	PN-EN 13163:2013-05E
Squareness, flatness	S5 ( $\pm 5$ mm/1m) P10 (10 mm)	EN 824 EN 825	
Flexural strength	BS $\geq 500$ kPa	EN 12089	
Compressive stress at 10% deformation	CS(10) $\geq 300$ kPa	EN 826	
Declared thermal conductivity coefficient $\lambda$	0,034 W/(m K)	EN 12667	
Reaction-to-fire class	EUROCLASS E	EN 11925-2	PN-EN 13501-1+A1:2010


## 8. Summary

The performance of the product identified above is in accordance with the set of declared performance. A declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

On behalf of the manufacturer, signed by:

VICE-PRESIDENT – Jakub Wójcik

Zduńska Wola 24.04.2018



**„IZODOM 2000 POLSKA” Sp. z o.o.**  
98-220 Zduńska Wola, ul. Ceramiczna 2A,  
tel. (43) 823-41-88, (43) 823-89-50  
tel. (43) 823-89-47, tel./fax (43) 823-23-68  
NIP 726-00-00-414; REGON 730192247



**Izodom 2000 Polska Sp. z o.o.**  
**Vice-president Jakub Wójcik**